

CELLAR PULSE

Uptime matters

Cellar Pulse **monitors all your technical installations** and ensures your equipments (drinks, CO₂, azote, compressors and other equipment in the cellar) are functioning the proper way.

Technical teams will be able to receive alerts and notifications as soon as a misfunction is detected.

- Equipment performance monitoring:
 - CO_
 - Coóling
 - Temperature
 - Pressure
 - Energy comsumpion
- Reduced losses & waste



Remotely monitor quality





Reference 03.53.24








DRINKCTEC

Dimensions



Main features

- 7" touch screen to view all measurements
- Customizable alerts
- Up to 4 temperature measurements
- Up to 4 pressure measurements

Technical features

Physical data height: 147 mm width: 215 mm depth: 88 mm weight: 1 kg


- Temperature sensors
 Temperature range: -50 to + 80°C
 Accuracy: +/- 1°C
- Pressure sensor (1x) Voltage: 5VDC Pressure range: 0-10 Bar Output voltage: 0-5 VDC Accuracy: +/- 0.1 Bar (ADC 12 bits)
- Operatin temperature Min: 2°C Max: 55°C
- Electrical data

mains voltage: male plug type F / type J 100-240 V frequency: 50 Hz power: 17.5 W

Back room requirements

The Cellar Pulse must be placed near your installations / storage place / kegs.

- 1 Cellar Pulse
- 2 Ambient temperature sensor
- 3 Ice bank temperature sensor
- 4 Compressor temperature sensor
- 5 Circulation return temperature sensor
- 6 CO, low pressure sensor
- $7 CO_{2}^{\prime}high$ pressure sensor
- 8 Compressor pressure sensor
- 9 Nitrogen high pressure sensor
- 10 Icecore series cooling system by Multiplex



Non-contractual layout



- 11 Compressor
- 12 Syrup pumps
- 13 Postmix Bag-in-Boxes
- 14 Nitrogen bottle
- 15 Kegs for spirits
- 16 Water filter
- 17 Water inlet
- 18 Beer or wine kegs
- 19 CO₂ bottle

DRINKCTEC